



Company: DEVON CANADA CORPORATION
Well Name: DEVON EAGLE PLAINS K-58
Field: EAGLE PLAINS
County: YUKON
Country: Canada
Province: YUKON

FileName: DEV631M.las	Data Presented by: Schlumberger DataView
Location: 66° 7' 34.8" N 300K586610136450 UWID 300K58661036450	Unique Well ID: 300K586610136450 Section: Township:
Elevations: Permanent Datum Elev: 599.299 M Permanent Datum: GROUND LEVEL Drilling Measured From: KELLY BUSHING Log Measured From: KELLY BUSHING	Kelly Bushing: 604.299 M Drilling Floor: 604.000 M Ground/sea Floor: 599.299 M Height Above Datum: 4.99999 M
Acquisition Date: 28-Mar-2005	Bit Size: 222.00 MM
Run Number: ONE	from: M to: 1278.00 M
Depth Driller: 1278.00 M	Csg size: Wt:
Depth Logger: 1278.00 M	from: to:
Top Log Interval: 10.00 M	Casing Bottom Logger:
Bottom Log Interval: 1272.50 M	Type Fluid in Hole:
Time Circ Stopped:	Dens: Vis:
Time Log at Bottom:	pH: Fid Loss: 7.50 C3
Max Recorded Temp:	Sample Source:
Unit Number:	Rm: @
Service Location:	Rmf: @
Recorded By:	Rmc: @
Witnessed By:	Borehole Salinity:

		MCFL STANDARD RESOLUTION INVADED ZONE RESISTIVITY (RXOZ)				
		0.2	OHMM	200		
		AIT-H TWOR FOOT RESISTIVITY A90 (AHT90)				
		0.2	OHMM	200		
MCFL MICRO NORMAL RESISTIVITY (HMNO)		AIT-H TWO FOOT RESISTIVITY A60 (AHT60)				
40	OHMM	0	0.2	OHMM	200	
MCFL MICRO INVERSE RESISTIVITY (HMIN)		AIT-H TWO FOOT RESISTIVITY A30 (AHT30)				
40	OHMM	0	0.2	OHMM	200	
SPONTANEOUS POTENTIAL (SP)		AIT-H TWO FOOT RESISTIVITY A20 (AHT20)			CABLE TENSION (TENS)	
-160	MV	40	0.2	OHMM	200	10000 N 0
HRCC CAL. CALIPER SC (HCAL)		AIT-H TWO FOOT RESISTIVITY A10 (AHT10)			HRDD STANDARD RESOLUTION FORMATION PHOTOELECTRIC FACTOR (PEFZ)	
6	MM	16	0.2	OHMM	200	0 B/E 10
CALIBRATED GAMMA-RAY SC (GR)						
0	GAPI	150				





