

Name of Contractor
 Location
 Operating No.
 Operation in Progress
 Spud Date
 Depth of well casing string
 Hoopstress
 Signature Signature Signature

N.B.: See Page 2 - Remarks re items checked as 'Not satisfactory' or 'No'.

I. WELLHEAD					
1. Well sealed	Yes	No	20. All work material in rig shelter	Yes	No
2. Four valves complete, up to and closed.	Yes	No	21. All valves and gauges checked for operation.	Yes	No
3. Location of wellsite with respect to natural & installed facilities	Yes	No	22. All work done on rig or in potentially dangerous areas.	Yes	No
4. Camp adequately contained	Yes	No	23. All breathing apparatus tested monthly & recorded in tour book.	Yes	No
5. Housekeeping	Yes	No	<u>II. RIG AREA</u>		
6. Radio communication in working order.	Yes	No	1. Mud tank capacity	Yes	No
7. Camp & kitchen facilities clean and sanitary.	Yes	No	2. Safety valve on pump discharge line	Yes	No
8. Adequate waste disposal	Yes	No	Type: <i>3" 100#</i>	Yes	No
9. Deviation surveys every 500' minimum and recorded in tour book	Yes	No	3. Mud weight relative to depth. <i>9.1 #</i>	Yes	No
			4. Gas analyzer.	Yes	No
			5. Location of mud tanks in rig shelter	Yes	No
			6. Gas level warning system. Type: <i>100#</i>	Yes	No
			7. Condition of Kelly hose.	Yes	No
			8. Mud mixing platform clean.	Yes	No
			9. Gaskets and nuts on fluid cylinder head and valve covers.	Yes	No
			10. Pressure rating of mud discharge line	Yes	No
			11. Mud gun anchors.	Yes	No
			<u>III. WORKING PLATFORM</u>		
			1. Condition of motors	Yes	No
			2. Safety net inlets greater than 40' from well bore.	Yes	No
			3. Safety cables greater than 40' from well bore.	Yes	No
			4. Where engine exhausts exceed 400°F., stack exhausts from area 75' from wellbore are installed	Yes	No
			5. Safety caps used on floor.	Yes	No
			6. Condition of fuel lines.	Yes	No
			7. Tank oil checked weekly and recorded in tour book.	Yes	No
			8. Other connections on engine exhausts working.	Yes	No
			<u>IV. WORKING PLATFORM</u>		
			1. Condition of motors	Yes	No
			2. Safety net inlets greater than 40' from well bore.	Yes	No
			3. Safety cables greater than 40' from well bore.	Yes	No
			4. Where engine exhausts exceed 400°F., stack exhausts from area 75' from wellbore are installed	Yes	No
			5. Safety caps used on floor.	Yes	No
			6. Condition of fuel lines.	Yes	No
			7. Tank oil checked weekly and recorded in tour book.	Yes	No
			8. Other connections on engine exhausts working.	Yes	No

