



APPLICATION TO ALTER CONDITION OF A WELL

This application form is to be submitted in triplicate to the District Conservation Engineer at least 45 days before commencement of operations.

Well Name: Western Minerals Chance YT No. 1 M-08 Area: Eagle Plains/Chance
 Coordinates: Lat: 56° 07' 45.99" Long: 137° 31' 27.30"
 Operator: Northern Cross (Yukon) Limited Contractor: To be determined
 Drilling Rig or Unit: _____ Depth: 2635.9 m KB
 Date ATDW Issued: February 25, 1959 Date of Last Operation: August 3, 1960
 Drilling Authority No.: 58

TYPE OF OPERATION

Recompletion and extended flow test

SUMMARY OF PROPOSED OPERATIONS (See attached Program)

For single zone completion procedures, drill out the cement retainer at 1316.7 mKB; under balance perforate the Chance Sand (1330.1 m - 1332.6 mKB); swab test formation; acidize if necessary; equip the well for hydraulic pumping; and place the Chance on test. For optional dual zone completion procedures drill out the retainer and abandonment cement plugs 1535.3 m to 1568.2 mKB, 1592.6 m to 1621.5 mKB and 1732.8 m to 1767.8 mKB to expose the Hart River Lower Limestone; acidize the Lower Limestone; set an injection packer; complete the Chance Sand (as above); and configure wellbore equipment for a dual zone completion which enables water injection into the Lower Limestone and hydraulic pumping production from the Chance Sand.

Signed: [Signature] Title: President
 Date: July 8, 1960 Company: Northern Cross (Yukon) Limited

APPROVAL

An approved copy of this notice should be posted at each wellsite.

Well Status
 Suspended **X**
 Completed
 Abandoned

Signed: [Signature]
 Chief Conservation Officer
 Date: Nov. 6, 1960
 ATDW No: WID. 153 File: 66-10-137-30
 UWI 300M086610137300